

GENSET MODEL				
Model	MG	TP 160 SS FI		
Mechanical version	Silenced steel she canopy, co	Silenced version with galvanized steel sheet and powder-painted canopy, compact base frame, with bunded tank and leak control		
Fuel Tank Capacity	lt.	360		
Rated technical data				
Prime Power (PRP)	kVA	160		
Prime Power (PRP)	KW	160		
Limited Power (LTP)	kVA	175		
Limited Power (LTP)	KW	140		
Rated Power Factor (cosф)		0.8		
Windings		Three phases Series Star		
Rated three-phase concatenated Voltage	V	400		
Rated phase-neutral voltage	V	230		
Rated frequency	Hz	50		
Fuel type		Diesel		
Dimensions And Noise				
Length	mm	3060		
Width	mm	1140		
Height	mm	2230		
Weight	Kg	2050		
Sound pressure 7 m.	dBA	68		
Fuel consumption				
Fuel Cons. at 100% (LTP)	l/h	42,2		
Fuel Cons. at 100% (PRP)	l/h	36,6		
Fuel Cons. at 75% (PRP)	l/h	27,5		
Fuel Cons. at 50% (PRP)	l/h	18		
General Alternator Data				
Alternator brand		STAMFORD		
Alternator model		UCI274F		
PRP Power	kVA	160		
LTP Power	kVA	175		
Winding		Three phases Series Star		
Terminals Number		12 nr		
IP Protection		23		
Electronic regulator		SX460		
Precision		± 1.50 %		
The	ifu the teek = i-	A. J		

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.



	General Engine Data		
	Engine brand		FPT IVECO
	Engine model		N67TM4
	Cylinders		6
	R.P.M.		1500
	Cubic capacity		6700
	Air intake		Turbo
	Standard voltage	Vdc	12
	Sae		-
	BMEP	kPa	1850
	Cooling		Water
	Flywheel P.R.P. Power	kW	149,7
	Flywheel Stand-by Power	kW	165
	Electronic regulator		On request
	Precision class		G3
	Oil quantity	lt.	17,2
	EU Stage		Not available

Standard Features

Hard wires connection protected

Electrical panel ComAp AMF25 mounted on board with safety cover Circuit breaker

Internal exhaust gas silencer and insulated manifold

Engine oil extraction pump and fuel decanter filter

12V Battery with battery switch

Bunded tank

Lifting hooks and side forklift pockets

Options factory installed

220V Electric pre-heater

KIT socket TPS01: 1x32A, 1x16A 3Ph

1x16A 1Ph + 1x16A Schuko

1x63A, 1x32A, 1x16A 3Ph

KIT socket TPS03: 1x16A 1Ph + 1x16A Schuko

125A breaker with adj. earth fault relay

Kit AMF and ATS panel

Predisposition for quick release fitting for external fuel tank

Oversize fuel tank

