



### GENSET MODEL

#### Model **MGTP 250 SS PI**

Mechanical version  
Silenced version with galvanized steel sheet and powder-painted canopy, compact base frame, with bunded tank and leak control

Fuel Tank Capacity                      lt.     360

#### Rated technical data

Prime Power (PRP)	kVA	250
Prime Power (PRP)	KW	200
Limited Power (LTP)	kVA	275
Limited Power (LTP)	KW	220
Rated Power Factor (cosφ)		0.8
Windings		Three phases Series Star

Rated three-phase concatenated Voltage	V	400
Rated phase-neutral voltage	V	230
Rated frequency	Hz	50
Fuel type		Diesel

#### Dimensions And Noise

Length	mm	3230
Width	mm	1140
Height	mm	2250
Weight	Kg	2860
Sound pressure 7 m.	dBA	78

#### Fuel consumption

Fuel Cons. at 100% (LTP)	l/h	60,7
Fuel Cons. at 100% (PRP)	l/h	55,5
Fuel Cons. at 75% (PRP)	l/h	41,6
Fuel Cons. at 50% (PRP)	l/h	28,9

#### General Alternator Data

Alternator brand		STAMFORD
Alternator model		UCDI274K
PRP Power	kVA	250
LTP Power	kVA	275
Winding		Three phases Series Star
Terminals Number		12 nr.
IP Protection		23
Electronic regulator		SX460
Precision		± 1.50 %

The company reserves the right to modify the technical specifications, items and design without notice.  
The images of the products are indicative for illustrative purposes only.

#### General Engine Data

Engine brand		PERKINS
Engine model		1506A-E88TAG3
Cylinders		6
R.P.M.		1500
Cubic capacity		8800
Air intake		Turbo
Standard voltage	Vdc	24
Sae		-
BMEP	kPa	2145
Cooling		Water
Flywheel P.R.P. Power	kW	222
Flywheel Stand-by Power	kW	244
Electronic regulator		Standard
Precision class		G2
Oil quantity	lt.	41
EU Stage		Not available

#### Standard Features

- Hard wires connection protected
- Electrical panel ComAp AMF25 mounted on board with safety cover
- Circuit breaker
- Internal exhaust gas silencer and insulated manifold
- Engine oil extraction pump and fuel decanter filter
- 12V Battery with battery switch
- Bunded tank
- Lifting hooks and side forklift pockets

#### Options factory installed

- 220V Electric pre-heater
- KIT socket TPS01: 1x32A, 1x16A 3Ph  
1x16A 1Ph + 1x16A Schuko
- 1x63A, 1x32A, 1x16A 3Ph
- KIT socket TPS03: 1x16A 1Ph + 1x16A Schuko  
125A breaker with adj. earth fault relay
- Kit AMF and ATS panel
- Predisposition for quick release fitting for external fuel tank
- Oversize fuel tank