Serkins®

GENSET MODEL				
Model	el MGTP 4			
Mechanical version	steel she canopy, co	Silenced version with galvanized steel sheet and powder-painted canopy, compact base frame, with bunded tank and leak control		
Fuel Tank Capacity	lt.	160		
Rated technical data				
Prime Power (PRP)	kVA	40		
Prime Power (PRP)	KW	32		
Limited Power (LTP)	kVA	44		
Limited Power (LTP)	KW	35,2		
Rated Power Factor (cosφ)		0.8		
Windings		Three phases Series Star		
Rated three-phase concatenated Voltage	V	400		
Rated phase-neutral voltage	V	230		
Rated frequency	Hz	50		
Fuel type		Diesel		
Dimensions And Noise				
Length	mm	2260		
Width	mm	1040		
Height	mm	1820		
Weight	Kg	1240		
Sound pressure 7 m.	dBA	61		
Fuel consumption				
Fuel Cons. at 100% (LTP)	l/h	12		
Fuel Cons. at 100% (PRP)	l/h	10,7		
Fuel Cons. at 75% (PRP)	l/h	8,2		
Fuel Cons. at 50% (PRP)	l/h	5,7		
General Alternator Data				
Alternator brand		STAMFORD		
Alternator model		S1L2-K		
PRP Power	kVA	40		
LTP Power	kVA	44		
Winding		Three phases Series Star		
Terminals Number		12 nr.		
IP Protection		23		
Electronic regulator		AS540		
Precision		± 1.00 %		
The company reserves the right to modi	fy the technic	al specifications items		

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.



	General Engine Data		
	Engine brand		PERKINS
	Engine model		1103A-33TG1
	Cylinders		3
	R.P.M.		1500
	Cubic capacity		3300
	Air intake		Turbo
	Standard voltage	Vdc	12
	Sae		-
	BMEP	kPa	1023
	Cooling		Water
	Flywheel P.R.P. Power	kW	41,3
	Flywheel Stand-by Power	kW	45,6
	Electronic regulator		On request
	Precision class		G2
	Oil quantity	lt.	8,3
	EU Stage		Not available

Standard Features

Hard wires connection protected

Electrical panel DSE 4520 mounted on board with safety cover

Circuit breaker

Internal exhaust gas silencer and insulated manifold

Engine oil extraction pump and fuel decanter filter

12V Battery with battery switch

Bunded tank

Lifting hooks and side forklift pockets

Options factory installed

220V Electric pre-heater

KIT socket TPS01: 1x32A, 1x16A 3Ph

1x16A 1Ph + 1x16A Schuko

1x63A, 1x32A, 1x16A 3Ph KIT socket TPSO3: 1x16A 1Ph + 1x16A Schuko

125A breaker with adj. earth fault relay

Kit AMF and ATS panel

Predisposition for quick release fitting for external fuel tank

Oversize fuel tank

