

DIESEL ENGINE DRIVEN GENERATING SET 1500 r.p.m.

STAGE 5
CERTIFIED



KOHLER



1500 RPM



NOISE level



WATER cooled



DIESEL



THREE phase



MGTP 60 SS KR

Code **RP354-60TS0**

TECHNICAL DATA

PRP Prime Power	kVA	60
LTP Limited Time Power	kVA	66
Prime Power (cos φ = 0,8)	kW	48
Limited Time P. (cos φ = 0,8)	kW	52,8
Three-phase Voltage	V	400
Single-phase Voltage	V	230
Power factor (cos φ)		0,8
Frequency	Hz	50
RPM		1500

GENERATOR

LINZ / MECC ALTE / STAMFORD	
Insulation Class	H
Mechanical protection	IP23

ENGINE

Type	KOHLER KDI 3404TCR CAC	
EU Emission Stage	Stage V	
N° cylinders	4	
Displacement	cm ³	3400
Speed regulation	Electrical	
Cooling	Water	
Fuel	Diesel	

FUEL CONSUMPTION

Fuel Tank capacity	lt.	232
Fuel consumption 75% load PRP	l/h	10,8
Running time	h	17

NOISE LEVEL

Noise level	Lwa	90
Acoustic pressure level 7m	dBA	65

DIMENSIONS & WEIGHT

Dry weight	Kg	1600
Dimensions (L. x W. x H.)	mm	2240 x 1196 x 1737

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.

DISTRIBUTION PANEL:

1x 63A 400V EEC with MCB
1x 32A 400V EEC with MCB
1x 32A 230V EEC with MCB + ELCB
1x 16A 230V EEC with MCB + ELCB
Hardwire
ELR

STANDARD FEATURES:

Built in fuel tank
Bunded tank
12V Battery
Battery switch
Forklift pocket
Central lifting eye
Exhaust gas silencer
Soundproof canopy
3 ways valve for external fuel tank connection

ON BOARD CONTROL PANEL EQUIPPED WITH:

DSE 7310
ON/OFF switch
Safety cover for DSE 7310 and ON/OFF switch
Main circuit breaker
Earth leakage relay
Remote start/stop connector
Emergency stop

OPTIONS

<input type="checkbox"/> Site tow trailer	<input type="checkbox"/> Road tow trailer
---	---