


## T-ZERO<sup>PRO</sup>

### POWER & INNOVATION



REMOTE  
telemetry



PEAK  
shaving



RENEWABLES  
Energy Connection



EASY  
handling



BATTERY  
technology



SINGLE  
phase



THREE  
phase



LITHIUM  
battery



PLUG  
& play

#### MGTP 45000/90 BP

Code **BP379-45TS2**

#### Technical data

Continuous power (VA)	45000
Overload 0,5s (W)	75000
Battery pack capacity (Wh)	93389
Capacity available DOD 80% (Wh)	74711
Voltage (V)	230/400
Frequency (Hz)	50

#### Inverter

Nominal power (VA)	15000
Q.ty	3
System voltage (V)	48
Max charging current (A)	200

#### Batteries

Type	LiFePO4
Q.ty	12
Nominal Voltage (V)	25,6
Nominal Capacity (Ah)	304
Cycle Life DOD 80%	> 4000

#### Distribution Panel

Inlet Plug	1x 63A-400V
	1x 63A-400V
Outlet Sockets	1x 32A-400V
	1x 16A-230V
Auto start connection cable	Standard

#### Performances

Running time (h) 25% load	8,5
Running time (h) 50% load	4,0
Running time (h) 75% load	2,5
Recharge time (h)	3,5
Recommended generator size (kVA)	55

#### Standard Features

- 5" Touch monitoring display controller
- Communication-centre device
- 48V/1000A BMS + Distributor to protect the batteries
- 4G/GPS Antenna + Modem
- Remote telemetry & management
- Auto recharge of the batteries from external generator
- Automatic peak shaving mode
- Sides forklift pockets & Central lifting hook
- Lockable control panel
- Main circuit breaker & Earth leakage relay
- Emergency Stop button

#### Available options

- MC4 connectors + MPPT solar charger for external solar panels
- Mat heating system for batteries to work in cold ambients
- 1x 125A-400V Inlet & Outlet

#### Dimension

Length (mm)	1960
Width (mm)	1350
Height (mm)	1520
Weight (Kg)	1700

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.