

T-ZERO^{PRO}

POWER & INNOVATION



BATTERY
technology



SINGLE
phase



LITHIUM
battery



EASY
handling

MGTP 3000/4 BP

Code **PP297-4MS1**

Technical data

Continuous power (VA)	3000
Overload 0,5s (W)	6000
Battery pack capacity (Wh)	3840
Capacity available DOD 80% (WH)	3072
Voltage (V)	230
Frequency (Hz)	50

Inverter

Nominal power (VA)	5000
Q.ty	3
System voltage (V)	12
Max charging current (A)	120

Batteries

Type	LiFe P04
Q.ty	1
Nominal Voltage (V)	12,8
Nominal Capacity (Ah)	300
Cycle Life DOD (80%)	→2500

Distribution Panel

Inlet Plug	1x 16A-230V
Outlet Sockets	1x 16A-230V

Performances

Running time (h) 25% load	5
Running time (h) 50% load	2,5
Running time (h) 75% load	1,5
Recharge time (h)	3
Recommended generator size (kVA)	3

Standard Features

Monitor for battery performances
MC4 connectors + MPPT solar charger for external solar panels
Main circuit breaker & Earth leakage relay
BMS to protect the batteries
Emergency Stop button
N. 4 extractable handles & Central lifting hook

Available Optionals

Mat heating system for batteries to work in cold ambients

Dimension

Length (mm)	800
Width (mm)	480
Height (mm)	530
Weight (Kg)	121

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.